

Features

- 0.3" (7.62mm) Digit Height
- Dual Digit Display
- Black/Grey Face , White Segment
- IC compatible, Easy assembly
- Dynamic drive connect
- RoHS Compliant, Pb Free

Description

The INND-SD30 series is a 0.3" dual digit display. It is a SMD type LED display which can be used in various applications.

Applications

- Consumer Electronics
- Industrial Equipment

Internal Circuit Diagram




Figure 1. INND-SD30 series Internal Circuit Diagram

Package Dimensions




Figure 2. INND-SD30 series Package Dimensions

Notes

1. Dimension in millimeter [inch], tolerance is ± 0.25 [0.010] and angle is $\pm 1^\circ$ unless otherwise noted.
2. Bending \leq Length * 1%.

All Light On Segments Feature & Pin Position




Figure 3. All Light On Segments Feature & Pin Position

Absolute Maximum Rating at 25°C (Note 1)

Product (Per Segment)	Emission Color	Technology	Pd (mW)	IF (mA)	IFP* (mA)	VR (V)	Derate From 25°C (mA/°C)	T _{OP} (°C)	T _{ST} (°C)
INND-SD30YGXX	Yellow Green	AlGaInP	70	25	90	5	0.33	-40°C~+105°C	-40°C~+105°C
INND-SD30YXX	Yellow	AlGaInP	70	25	90	5	0.33	-40°C~+105°C	-40°C~+105°C
INND-SD30AXX	Amber	AlGaInP	70	25	90	5	0.33	-40°C~+105°C	-40°C~+105°C
INND-SD30RXX	Red	AlGaInP	70	25	90	5	0.33	-40°C~+105°C	-40°C~+105°C
INND-SD30DRXX	Deep Red	AlGaInP	70	25	90	5	0.33	-40°C~+105°C	-40°C~+105°C
INND-SD30GXX	Green	InGaN	114	30	100	5	0.4	-40°C~+105°C	-40°C~+105°C
INND-SD30BXX	Blue	InGaN	114	30	100	5	0.4	-40°C~+105°C	-40°C~+105°C

Notes

1. Condition for IFP is pulse of 1/10 duty and 0.1msec width

Electrical Characteristics $T_A = 25^\circ\text{C}$ (Note 1)

Product (Per Segment)	Emission Color	$V_F(\text{V})@20\text{mA}$			$\lambda(\text{nm})@20\text{mA}$		$I_V^*(\text{mcd})@10\text{mA}$			$I_R(\mu\text{A})@V_R=5\text{V}$	$I_{V-M}@I_F=10\text{mA}$
		min	typ.	max	λ_D	λ_P	min	typ.	max	max	max
INND-SD30YGXX	Yellow Green	-	2.0	2.8	570	572	-	2	-	100	2:1
INND-SD30YXX	Yellow	-	2.0	2.8	590	592	-	8	-	100	2:1
INND-SD30AXX	Amber	-	2.0	2.8	605	612	-	9	-	100	2:1
INND-SD30RXX	Red	-	2.0	2.8	630	644	-	4	-	100	2:1
INND-SD30DRXX	Deep Red	-	2.0	2.8	645	660	-	2	-	100	2:1
INND-SD30GXX	Green	-	3.2	3.8	525	-	-	37	-	100	2:1
INND-SD30BXX	Blue	-	3.2	3.8	465	-	-	7	-	50	2:1

Notes

- Performance guaranteed only under conditions listed in above tables.

ESD Precaution

ATTENTION: Electrostatic Discharge (ESD) protection



The symbol above denotes that ESD precaution is needed. ESD protection for GaP and AlGaAs based chips is necessary even though they are relatively safe in the presence of low static-electric discharge. Parts built with AlInGaP, GaN, or/and InGaN based chips are STATIC SENSITIVE devices. ESD precaution must be taken during design and assembly.

If manual work or processing is needed, please ensure the device is adequately protected from ESD during the process.

Please be advised that normal static precautions should be taken in the handling and assembly of this device to prevent damage or degradation which may be induced by electrostatic discharge (ESD).


Characteristic Curves for YG, Y, A, R, DR, G


Fig 1. Forward Current vs. Forward Voltage




Fig 2. Relative Intensity vs. Forward Current




Fig 3. Forward Voltage vs. Temperature




Fig 4. Relative Intensity vs. Temperature




Fig 5. Relative Intensity vs. Wavelength




Fig 6. Forward current vs. Temperature

Characteristic Curves for B




Fig 1. Forward Current vs. Forward Voltage




Fig 2. Relative Intensity vs. Forward Current




Fig 3. Forward Voltage vs. Temperature




Fig 4. Relative Intensity vs. Temperature




Fig 5. Relative Intensity vs. Wavelength





Fig 6. Forward current vs. Temperature

Ordering Information

Product	Emission Color	Technology	I*V(mcd) @10mA	VF(V) @20mA	Polarity	Face Color	Orderable Part Number
INND-SD30YGXX	Yellow Green	AlGaInP	2	2.0	Common Anode	Black	INND-SD30YGAB
					Common Cathode	Black	INND-SD30YGCB
					Common Anode	Grey	INND-SD30YGAG
					Common Cathode	Grey	INND-SD30YGCG
INND-SD30YXX	Yellow	AlGaInP	8	2.0	Common Anode	Black	INND-SD30YAB
					Common Cathode	Black	INND-SD30YCB
					Common Anode	Grey	INND-SD30YAG
					Common Cathode	Grey	INND-SD30YCG
INND-SD30AXX	Amber	AlGaInP	9	2.0	Common Anode	Black	INND-SD30AAB
					Common Cathode	Black	INND-SD30ACB
					Common Anode	Grey	INND-SD30AAG
					Common Cathode	Grey	INND-SD30ACG
INND-SD30RXX	Red	AlGaInP	4	2.0	Common Anode	Black	INND-SD30RAB
					Common Cathode	Black	INND-SD30RCB
					Common Anode	Grey	INND-SD30RAG
					Common Cathode	Grey	INND-SD30RCG

Product	Emission Color	Technology	I*V(mcd) @10mA	VF(V) @20mA	Polarity	Face Color	Orderable Part Number
INND-SD30DRXX	Deep Red	AlGaInP	2	2.0	Common Anode	Black	INND-SD30DRAB
					Common Cathode	Black	INND-SD30DRCB
					Common Anode	Grey	INND-SD30DRAG
					Common Cathode	Grey	INND-SD30DRCG
INND-SD30GXX	Green	InGaN	37	3.2	Common Anode	Black	INND-SD30GAB
					Common Cathode	Black	INND-SD30GCB
					Common Anode	Grey	INND-SD30GAG
					Common Cathode	Grey	INND-SD30GCG
INND-SD30BXX	Blue	InGaN	7	3.2	Common Anode	Black	INND-SD30BAB
					Common Cathode	Black	INND-SD30BCB
					Common Anode	Grey	INND-SD30BAG
					Common Cathode	Grey	INND-SD30BCG

Label Specifications




Inolux P/N:

I	N	N	D	-	S	D	3	0	X	X	X	-	X	X	X	X	
Inolux		Display Type			Display Type		Dimension		Color	Polarity		Face Color		Customized Stamp-off			
		ND = Numeric Display			S: SMD Type D: Dual		30 = 0.30" Display Height		YG: 570 nm Y: 590 nm A: 605 nm R: 624 nm DR: 660 nm G: 520 nm B: 470 nm	A = Common Anode C=Common Cathode		B = Black G = Grey					

Lot No.:

Z	2	0	1	7	01	24	001
Internal Tracker	Year (2017, 2018,)				Month	Date	Serial

Reflow Soldering



Soldering Iron

Basic Spec is ≤ 4 sec. when 260°C (+10°C → -1 second). Power dissipation of Iron should be less than 15W. Surface temperature should be under 230°C

Rework

Rework should be completed within 4 second under 245°C

Revision History

Changes since last revision	Page	Version No.	Revision Date
Initial Release		1.0	12-25-2019

DISCLAIMER

INOLUX reserves the right to make changes without further notice to any products herein to improve reliability, function or design. INOLUX does not assume any liability arising out of the application or use of any product or circuit described herein; neither does it convey any license under its patent rights, nor the rights of others.

LIFE SUPPORT POLICY

INOLUX's products are not authorized for use as critical components in life support devices or systems without the express written approval of the President of INOLUX or INOLUX CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user.
2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.