

### Featured

- 1204 0.8mm SMD LED
- High Brightness
- AllnGaP / InGaN Technology
- High Reliability
- Clear Lens

### Applications

- Consumer Electronics
- Wearables
- Automobile After Market
- Industrial Equipment

### Description

The IN-S124TCRRGB is a 1204 package RGB LED with reverse mount and versatile design capabilities. It is a PCB type molding style LED which can be used in various applications.

### Recommended Solder Pattern




Figure 1. IN-S124TCR Solder Pattern

### Package Dimensions in mm




Figure 2. IN-S124TCR Package Dimensions

## Absolute Maximum Rating at 25°C (Note 1)

Product	Emission Color	$P_d$ (mW)	$I_F$ (mA)	$I_{FP}^*$ (mA)	$V_R$ (V)	$T_{OP}$ (°C)	$T_{ST}$ (°C)
IN-S124TCRRGB	Red	48	20	40	5	-40°C~+85°C	-40°C~+100°C
	Green	78	20	40	5	-40°C~+85°C	-40°C~+100°C
	Blue	78	20	60	5	-40°C~+85°C	-40°C~+100°C

### Notes

1. Condition for IFP is pulse of 1/10 duty and 0.1msec width

### ESD Precaution

ATTENTION: Electrostatic Discharge (ESD) protection



The symbol above denotes that ESD precaution is needed. ESD protection for GaP and AlGaAs based chips is necessary even though they are relatively safe in the presence of low static-electric discharge. Parts built with AlInGaP, GaN, or/and InGaN based chips are STATIC SENSITIVE devices. ESD precaution must be taken during design and assembly. If manual work or processing is needed, please ensure the device is adequately protected from ESD during the process.

Please be advised that normal static precautions should be taken in the handling and assembly of this device to prevent damage or degradation which may be induced by electrostatic discharge (ESD).

**Electrical Characteristics**  $T_A = 25^\circ\text{C}$  (Note 1)

Product	Emission Color	$I_F(\text{mA})$	$V_F(\text{V})$		$\lambda (\text{nm})$			Viewing Angle	$I_v(\text{mcd})$
			typ.	max	$\lambda_D$	$\lambda_P$	$\Delta\lambda$	$2\theta_{1/2}$	typ.
IN-S124TCRRGB	Red	20	2.0	2.4	624	632	20	X = 140 Y = 125	71.5
	Green	20	3.3	3.9	525	520	30	X = 140 Y = 125	285.0
	Blue	20	3.3	3.9	470	468	40	X = 140 Y = 125	71.5

**Notes**

1. Performance guaranteed only under conditions listed in above tables.

**Luminous Intensity (Iv) Bin:**

Color	Bin Code	Spec. Range
Red	N	28.5-45.0 mcd
	P	45.0-71.5 mcd
	Q	71.5-112.5 mcd
	R	112.5-180.0 mcd
Green	R	112.5-180.0 mcd
	S	180.0-285.0 mcd
	T	285.0-360.0 mcd
	U	360.0-450.0 mcd
Blue	N	28.5-45.0 mcd
	P	45.0-71.5 mcd
	Q	71.5-112.5 mcd
	R	112.5-180.0 mcd

Note: It maintains a tolerance of  $\pm 10\%$  on luminous intensity

**Color Bin:**






Color	Bin Code	Spec. Range
Red	AD	615.0-630.0 nm
Green	A	515.0- 520.0 nm
	B	520.0- 525.0 nm
	C	525.0- 530.0 nm
	D	530.0- 535.0 nm
	E	535.0-540.0 nm
Blue	AA	460.0-465.0nm
	AB	465.0-470.0 nm
	AC	470.0-475.0 nm
	AD	475.0-480.0 nm

Note: It maintains a tolerance of  $\pm 0.5\text{nm}$  on color





**Forward Voltage (Vf) Bin:**

<b>Color</b>	<b>Bin Code</b>	<b>Spec. Range</b>
<b>Red</b>	<b>E18</b>	<b>1.6~2.4 V</b>
<b>Green</b>	<b>G8</b>	<b>2.7-2.9 V</b>
	<b>H7</b>	<b>2.9-3.1 V</b>
	<b>H8</b>	<b>3.1-3.3 V</b>
	<b>J7</b>	<b>3.3-3.5 V</b>
	<b>J8</b>	<b>3.5-3.7 V</b>
	<b>K7</b>	<b>3.7-3.9 V</b>
<b>Blue</b>	<b>G8</b>	<b>2.7-2.9 V</b>
	<b>H7</b>	<b>2.9-3.1 V</b>
	<b>H8</b>	<b>3.1-3.3 V</b>
	<b>J7</b>	<b>3.3-3.5 V</b>
	<b>J8</b>	<b>3.5-3.7 V</b>
	<b>K7</b>	<b>3.7-3.9 V</b>


Note: It maintains a tolerance of  $\pm 0.05V$  on forward voltage measurements

**Typical Characteristic Curves – YG, Y, A, R**


### Typical Characteristic Curves – B, G, W



### Typical Characteristic Curves – Radiation Pattern




### Ordering Information

Product	Emission Color	Technology	Test Current $I_F$ (mA)	Luminous Intensity $I_V$ (mcd) (Typ.)	Forward Voltage $V_F$ (V) (Typ.)	Orderable Part Number
IN-S124TCRRGB	Red	AllnGaP	20	71.5	2.0	IN-S124TCRRGB
	Green	InGaN	20	285.0	3.3	
	Blue	InGaN	20	71.5	3.3	



**Label Specifications**




**Inolux P/N:**

I	N	-	S	1	2	4	T	C	R			R	G	B	-	X	X	X	X
Inolux SMD			Material	Package			Variation		Orientation	Current	Lens	Color				Customized Stamp-off			
			S = PCB Type	124TC = 3.2 x 1.2 x 0.5mm Tri-chip					R = Reverse Mount	(Blank) = 20mA	(Blank) = Clear U = Diffused	R=624nm G=525nm B=470nm							


**Lot No.:**


Z	2	0	1	7	01	24	001
Internal Tracker	Year (2017, 2018, .....)				Month	Date	Serial

**Packaging Information: 3000pcs Per Reel**
**Tape Dimension**


Part No.	Dim. A	Dim. B	Dim. C	Q'ty/Reel
IN-S124TCRRGB	3.4±0.10	1.42±0.10	1.37±0.10	3K

Unit: mm

**Reel Dimension**


**Packing Dimension**


5 boxes per carton are available depending on shipment quantity.

	Specification	Material	Quantity
Carrier tape	Per EIA 481-1A specs	Conductive black tape	3000pcs per reel
Reel	Per EIA 481-1A specs	Conductive black	
Label	IN standard	Paper	
Packing bag	220x240mm	Aluminum laminated bag/ no-zipper	One reel per bag
Carton	IN standard	Paper	Non-specified

**Others:**


Each immediate box consists of 5 reels. The 5 reels may not necessarily have the same lot number or the same bin combinations of  $I_v$ ,  $\lambda_D$  and  $V_f$ . Each reel has a label identifying its specification; the immediate box consists of a product label as well.

## Dry Pack

All SMD optical devices are **MOISTURE SENSITIVE**. Avoid exposure to moisture at all times during transportation or storage. Every reel is packaged in a moisture protected anti-static bag. Each bag is properly sealed prior to shipment.

Upon request, a humidity indicator will be included in the moisture protected anti-static bag prior to shipment.


The packaging sequence is as follows:



## Reflow Soldering

- Recommended tin glue specifications: melting temperature in the range of 178~192 °C
- The recommended reflow soldering profile is as follows (temperatures indicated are as measured on the surface of the LED resin):

Lead-free Solder Profile



## Precautions

- Avoid exposure to moisture at all times during transportation or storage.
- Anti-Static precaution must be taken when handling GaN, InGaN, and AlInGaP products.
- It is suggested to connect the unit with a current limiting resistor of the proper size. Avoid applying a reverse voltage.
- Avoid operation beyond the limits as specified by the absolute maximum ratings.
- Avoid direct contact with the surface through which the LED emits light.
- If possible, assemble the unit in a clean room or dust-free environment.

## Reworking

- Rework should be completed within 5 seconds under 260 °C.
- The iron tip must not come in contact with the copper foil.
- Twin-head type is preferred.

## Cleaning

Following are cleaning procedures after soldering:

- An alcohol-based solvent such as isopropyl alcohol (IPA) is recommended.
- Temperature x Time should be 50°C x 30sec. or <30°C x 3min
- Ultra sonic cleaning: < 15W/ bath; bath volume ≤ 1liter
- Curing: 100 °C max, <3min

## Cautions of Pick and Place

- Avoid stress on the resin at elevated temperature.
- Avoid rubbing or scraping the resin by any object.
- Electro-static may cause damage to the component. Please ensure that the equipment is properly grounded. Use of an ionizer fan is recommended.

## Revision History

Changes since last revision	Page	Version No.	Revision Date
Initial Release		1.0	04-10-2017
Updated	1	1.1	10-25-2022
Updated	10	1.2	05-29-2024

## DISCLAIMER

INOLUX reserves the right to make changes without further notice to any products herein to improve reliability, function or design. INOLUX does not assume any liability arising out of the application or use of any product or circuit described herein; neither does it convey any license under its patent rights, nor the rights of others.

## LIFE SUPPORT POLICY

INOLUX's products are not authorized for use as critical components in life support devices or systems without the express written approval of the President of INOLUX or INOLUX CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user.
2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.